

Featuring lithium iron phosphate (LFP) battery technology for enhanced safety and reliable performance, GoodWe's HV Lynx D Series has been especially designed to facilitate a wide capacity range to meet the needs of residential solar power systems. Featuring stackable, self-detecting battery modules, the system is flexible and easy to install, allowing you to mix new and old battery modules for future expandable needs. Utilize more potential from solar energy by combining Lynx D battery with GoodWe hybrid inverters and any smart-grid ready household appliances to gain independance and reduce your energy costs with unintrerupted power supply.



Reliable performance (LFP battery cell)



Up to 8 stackable modules (40kWh)



Remote diagnosis and update via inverter





| Technical Data | | LX D5.0-10 |
|----------------------------------|----------------|---|
| Usable Energy (kWh)*1 | | 5 |
| Cell Type | | LFP (LiFePO ₄) |
| Nominal Voltage (V) | | Charge: 435; Discharge: 380 |
| Output Voltage (V) | | 320 ~ 480 |
| Nominal Power (kW) | | 3 |
| Peak Power | | 5kW, 10s |
| Operating Temperature Range (°C) | | Charge: 0 ~ +53; Discharge: -20 ~ +53 |
| Relative Humidity | | 0 - 95% |
| Max. Operating Altitude (m) | | 4000 |
| Communication | | CAN |
| Weight (kg) | | 52 |
| Dimensions (W × H × D mm) | | 700 × 380 × 170 |
| Ingress Protection Rating | | IP66 |
| Mounting Method | | Floor stacked / Wall-mounted |
| Standard and Certification | Safety | IEC62619, IEC60730, VDE2510-50, CE, CEC |
| | EMC | CE, RCM |
| | Transportation | UN38.3 |

^{*1:} Test conditions,100% DOD,0.2C charge & discharge at +25 ±3°C for battery system at beginning life. System Usable Energy may vary with different Inverter. *: Please visit GoodWe website for the latest certificates.